


# NAH 100 L2-4 IE3

### Abmessungen Drehstrom-Asynchronmotor / dimensions three phase asynchron motor **IM B5** (mm)



## Technische Daten / technical dates

Typ / type	NAH	100 L2-4 IE3	Nennmoment / rated torque	(Nm)	20,0
Leistung / power	(kW)	3,0	Anlaufstrom-Nennstrom / starting current-rated current	(Ia/In)	7,2
Betriebsart / duty		S1	Anzugsmoment-Nennmoment starting torque-rated torque	(Ma/Mn)	2,6
Nenndrehzahl/ speed (50 Hz)	(min <sup>-1</sup> )	1430	Kippmoment-Nennmoment Pull-out torque	(Mk/Mn)	3,5
Nennstrom / rated current 400 V	(A)	6,32	Massenträgheitsmoment / moment of inertia	(kgm <sup>2</sup> )	0,01213
Spannung / voltage (+/-5%)	(V)	230/400 (Δ/Y)	Umgeb.-temp./ ambient temperature		40°C
Frequenz / frequency	(Hz)	50	Lager / bearing	(DE) (NDE)	6206 ZZ 6206 ZZ
Wirkungsgrad / efficiency	(%)	87,9	Schallpegel / noise level	dB (A)	64
Leistungsfaktor / power factor	(cos φ)	0,78	Gewicht / weight	(kg)	28,5
Schutzart / protection		IP55			
Isolationsklasse / insulation class		F			

### Schaltplan / connection diagram

